

Crown Copyright Reserved



ARMY
CODE NO.

14618

57
Vocabulary
7053

RESTRICTED

The information given in this document is not to be communicated, either directly or indirectly, to the Press, or to any person not authorized to receive it.

Vocabulary of Army Ordnance Stores

SECTION Z 9

SECONDARY BATTERIES AND NON-ROTATING BATTERY CHARGING EQUIPMENT

1965

(Supersedes Code No. 12617)

By Command of the Defence Council.

A handwritten signature in black ink, appearing to read 'Henry [unclear] [unclear]'. The signature is written in a cursive style.

MINISTRY OF DEFENCE

September, 1965

RESTRICTED

VOCABULARY OF ARMY ORDNANCE STORES

SECTION Z9

FOREWORD

1. Demands for further copies of this publication, or amendments thereto will be passed through the normal channels of supply for Ministry of Defence publications.

2. Amendments will be published as replacement pages.

3. Items appearing in italics are OBSOLESCEANT.

4. The NATO system of cataloguing utilizes a 13-digit coding structure; the 13 digits are broken down into groups as follows:-

- (a) *The N.A.T.O. class* is indicated by the first group of four digits. This shows the range of store to which the catalogued item belongs.
- (b) *The NATION Code* is indicated by the next group of two digits. This shows the NATO country of origin, which has codified the item.
- (c) *The NATIONAL identification number* is indicated by the last seven digits. This shows the actual item identification number. The hyphen between the third and fourth digits is inserted as an aid to memory.

Information for the Scanned Document

This document is provided with a manual, non-searchable, index following the last tabulated page

The page numbers in the index refer to the numbers in the original document

In order to preserve the column headings the two facing pages of the original document have been scanned as one. The original page numbers are thus shown at the top as page (n), and at the bottom as page (n+1)

SECTION 29

BATTERIES, SECONDARY

These are listed in voltage orders-

BATTERIES, Secondary, Alkaline on pages 4 and 5

BATTERIES, Secondary, acid/lead acid on pages 5 to 13

| Cat. No. | Voltage | Capacity (Ah.) at 10 hr. rate Unless stated | Approx. Weight : o/a dim. filled (in.) | | | Vent | Container | Terminals | Remarks | |
|------------------|---------|------------------------------------------------------|----------------------------------------------|----|---|------|------------|------------------------|--------------------------|---------------------------------|
| | | | lb. | L | W | | | | | H |
| Z9/ | | | | | | | | | | |
| 6140-99-910-1802 | 1.2 | 10 | 2 | 3 | 1 | 5 | spillable | steel | studs and nuts | Dry, uncharged |
| 6140-99-900-3149 | 1.2 | 10 | - | - | - | - | - | - | - | |
| 6140-99-910-1803 | 1.2 | 25 | 4 | 4 | 1 | 9 | non-splash | steel | studs and nuts | Dry, uncharged |
| 6140-99-910-1815 | 1.2 | 75 | 9 | 5 | 2 | 11 | non-splash | steel | studs and nuts | |
| 6140-99-910-1809 | 2.4 | 7.5 | 3 | 2 | 2 | 5 | non-splash | steel | studs and nuts | |
| 6140-99-910-1810 | 2.4 | 10 | 3 | 3 | 2 | 6 | non-spill | steel | spring-loaded plunger | |
| 6140-99-943-9413 | 6 | 7 | 7 | 10 | 2 | 7 | non-splash | steel in wood crate | studs and nuts | Partly discharge and emptied |
| ZJ 00127 | 6 | 18 | 14 | 9 | 2 | 8 | non-splash | steel | studs and nuts | W. cover |
| 6140-99-910-1816 | 6 | 75 | 65 | 15 | 6 | 12 | non-splash | steel in wood crate | studs and nuts | Dry, uncharged |

| | | | | | | | | | | |
|------------------|-----|-----------------------------|-----|-------------------|---|----|--------------------|---------------------------|----------------------------|---------------------------------------|
| 6140-99-110-2470 | 7.2 | 3 | 2 | 5 | 2 | 2 | non-splash | plastic outer | socket | NiCd, filled and fully charged |
| 6140-99-949-9955 | 24 | 35 (1 hr.) | 78 | - | - | - | - | steel | socket | Filled and uncharged |
| 6140-99-910-1819 | 12 | 25 | 42 | 18 | 5 | 9 | non-splash | steel in wood crate | studs and nuts | Dry, uncharged |
| AN 605 | 12 | 25 | 50 | 20 | 7 | 11 | non-splash | steel in wood crate | | 910-1819 in steel box w. lid |
| ZB 14595 | 36 | 210 (6 hr.) | 546 | 4 crates, each | | 11 | non-splash | steel in 4 wood crates | studs and nuts | Traction |
| Acid/lead acid | | | | | | | | | | |
| 6140-99-900-7951 | 2 | 0.4 | 1 | 1 | 1 | 2 | sealed, no vent | polystyrene | metal strip | |
| 5J 3306 | 2 | 1.5 | 1 | 4 | 1 | 2 | non-spill | polystyrene | studs and nuts | |
| ZB 0970 | 2 | 7 | 1 | 3 | 1 | 5 | non-spill | celluloid | hex, contacts | |
| 6140-99-910-1501 | 2 | 7 | 1 | 3 | 1 | 5 | non-spill | celluloid | studs and nuts | Dry, uncharged |
| ZB 11277 | 2 | 10 (20 hr.) 12 (100 hr.) | 3 | 3 dia. | | 4 | non-spill | polythene | spring type | |
| 6140-99-910-1502 | 2 | 10 | 11 | 5 | 3 | 12 | non-splash | glass | lugs | Dry, uncharged |
| WB 2673 | 2 | 11 | 3 | 3 dia. | | 6 | non-spill | celluloid | spring loaded plungers | Jelly electrolyte |
| ZB 10064 | 2 | 11 | 2 | 5 | 3 | 3 | non-spill | celluloid | studs and nuts | |
| ZJ 00008 | 2 | 12 | 3 | 6 | 3 | 3 | non-spill | glass | studs and nuts | |
| 6140-99-900-2672 | 2 | 16 | 5 | 5 | 2 | 8 | non-spill | hard rubber | studs and nuts | Dry, uncharged |
| 6140-99-910-1504 | 2 | 20 | 16 | 5 | 5 | 12 | non-splash | glass | lugs | Dry, uncharged |
| ZJ 00283 | 2 | 20 | - | 2 | 3 | 6 | non-splash | glass | screw type insul. knobs | |
| 6140-99-910-1506 | 2 | 50 | 39 | 8 | 5 | 18 | non-splash | glass | lugs | Dry, uncharged |
| ZB 0955 | 2 | 75 | 14 | 7 | 4 | 7 | non-splash | hard rubber | studs and nuts | c/w. steel carrier and wood handle |

SECTION Z9

BATTERIES, SECONDARY - continued

| Cat. No. | Voltage | Capacity (Ah.) at 10 hr. rate unless stated | Approx. Weight : o/a dim. filled (in.) | | | | Vent | Container | Terminals | Remarks |
|------------------|---------|------------------------------------------------------|----------------------------------------------|-------|-------|--------|--------------|-------------------------|---------------|-----------------------------|
| | | | lb. | L | W | H | | | | |
| Z9/ | | | | | | | | | | |
| 6140-99-910-1509 | 2 | 75 | 56 | 8 | 7 | 18 | non-splash | glass | lugs | Dry, uncharged |
| ZJ 00176 | 2 | 99 | 16 | 7 | 4 | 12 | non-splash | hard rubber in steel | Spring type | Lansing Bagnall Traction |
| 6140-99-910-1510 | 2 | 125 | 84 | 10 | 7 | 18 | non-splash | glass | lugs | Dry, uncharged |
| 6140-99-910-1511 | 2 | 200 | - | 10 | 9 | 15 | open type | glass | lugs | Dry, uncharged |
| ZJ 00181 | 2 | 206 (5 hr.) | 39 | 3 | 6 | 19 | non-splash | hard rubber | thimble | Traction |
| 6140-99-900-6133 | 2 | 216 (5 hr.) | 35 | 3 | 6 | 19 | non-spill | hard rubber outer | SMMT taper | Dry, uncharged |
| 6140-99-900-2321 | 2 | 220 (5 hr.) | 38 | 3 1/8 | 6 1/2 | 19 1/2 | spillable | rubber case | post type | Dry, uncharged |
| ZJ 00253 | 2 | 224 (5 hr.) | 45 | 5 | 6 | 15 | bayonet type | hard rubber | taper thimble | Traction |
| ZJ 00270 | 2 | 240 (5 hr.) | 48 | 3 | 6 | 21 | anti-splash | hard rubber | thimble | Traction |
| ZJ 00188 | 2 | 240 (5 hr.) | 49 | 4 | 6 | 19 | non-splash | hard rubber | thimble | Traction |
| 6140-99-910-1513 | 2 | 250 | - | 11 | 9 | 15 | open type | glass | lugs | Dry, uncharged |
| ZJ 00174 | 2 | 252 (5 hr.) | 49 | 4 | 6 | 18 | non-splash | hard rubber | thimble | Traction |
| 6140-99-910-1514 | 2 | 300 | - | 13 | 8 | 15 | open type | glass | lugs | Dry, uncharged |
| 6140-99-104-0636 | 2 | 300 | - | - | - | - | - | - | - | Wet charged |
| ZJ 00234 | 2 | 463 (5 hr.) | 86 | 8 | 6 | 19 | non-splash | hard rubber | thimble | Traction |

| | | | | | | | | | | |
|------------------|-------|-------------|-----|--------|---|----|------------|----------------------------------------------------------|---------------------------|----------------------------|
| -B 13a32 | 4 | 8 | 4 | 3 dia. | 7 | | non-spill | celluloid | spring loaded plungers | Traction |
| 6B (53b) | 6 | 16 | 16 | 8 | 5 | 9 | non-spill | composition in wood case | socket | |
| 6140-99-900-3265 | 6 | 16 | 17 | 8 | 5 | 9 | non-splash | wood outer | socket | Dry, uncharged |
| ZB 13731 | 6 | 57 | 32 | 9 | 7 | 8 | non-splash | hard rubber | J/NIE taper | |
| ZB 13729 | 6 | 60 | 35 | 10 | 7 | 8 | non-splash | hard rubber | SMMT taper | |
| ZJ 00193 | 6 | 75 | 42 | 9 | 7 | 8 | non-splash | hard rubber | SMMT taper | |
| ZB 13680 | 6 | 76 | 40 | 9 | 7 | 9 | non-splash | hard rubber | SMMT taper | |
| 6140-99-910-1519 | 6 | 85 | 55 | 13 | 7 | 9 | non-spill | composition permanently moulded into metal case | socket | Dry, uncharged |
| 6140-99-910-1522 | 6 | 102 | 53 | 11 | 7 | 9 | non-splash | hard rubber | SMMT taper | Dry, uncharged |
| ZJ 00118 | 6 | 130 | 80 | 15 | 5 | 14 | non-splash | composition | SMMT taper | |
| 6140-99-910-1524 | 6 | 170 | 110 | 16 | 8 | 13 | non-splash | composition permanently moulded into metal case | studs and nuts | Dry, uncharged |
| 6140-99-910-1545 | 6 | 170 | 110 | 16 | 8 | 13 | non-splash | composition permanently moulded into metal case | studs and nuts | Dry, charged |
| 5J 3305 | 6 + 6 | 1.5 | 2 | 4 | 3 | 2 | non-spill | polystyrene | studs and nuts | |
| 6140-99-910-1529 | 10 | 5 (100 hr.) | 6 | 7 | 3 | 5 | non-splash | glass | studs and nuts | Dry, uncharged |
| 6140-99-900-8938 | 12 | 88 | 109 | 17 | 7 | 12 | spillable | metal case | tapered post | Traction, dry uncharged |
| ZJ 00276 | 12 | 99 | 112 | 17 | 7 | 12 | non-splash | hard rubber in steel case | Lansing Bagnall | Traction |
| ZJ 00128 | 12 | 99 | 112 | 17 | 7 | 12 | non-splash | hard rubber in steel case | Lansing Bagnall | Traction |

SECTION 29

BATTERIES, SECONDARY - continued

| Cat. No. | Voltage | Capacity (Ah.) at 10 hr. rate unless stated | Approx. Weight : o/a dim, filled (in.) | | | Vent | Container | Terminals | Remarks | |
|------------------|---------|---------------------------------------------|----------------------------------------|------------------------------------|----|------|------------|------------------------------------------------|-----------------|------------------|
| | | | lb. | L | W | | | | | H |
| <i>29/</i> | | | | | | | | | | |
| ZJ 00300 | 12 | 99 | - | 17 | 7 | 12 | non-spill | metal outer case | tapered post | Dry, uncharged |
| 6140-99-110-2684 | 12 | 99 (5 hr.) | 94 | 17 | 7 | 12 | non-spill | hard rubber | tapered post | Dry, uncharged |
| ZJ 00232 | 12 | 112 | 115 | 23 | 8 | 10 | non-splash | hard rubber | SMMT taper | |
| ZJ 00175 | 12 | 120 | 109 | 20 | 9 | 10 | non-splash | composition permanently moulded into wood case | SMMT taper | |
| ZJ 00280 | 16 | 206 (5 hr.) | 368 | 27 | 8 | 23 | non-splash | hard rubber in wood crate | FSV 2 hole type | Traction |
| 6140-99-900-5863 | 16 | 216 (5 hr.) | 390 | 27 | 8 | 23 | non-spill | wood outer | SMMT taper | Dry, uncharged |
| ZB 0276 | 24 | 170 | 470 | 37 | 15 | 16 | non-splash | composition in wood case w. lid | socket | W. carrying hand |
| ZJ 00285 | 24 | 315 (5 hr.) | - | in 4 crates totalling o/a 43 21 13 | | | non-splash | hard rubber in 4 wood crates | lugs | Traction |
| ZJ 00212 | 30 | 125 (5 hr.) | 400 | 34 | 13 | 14 | non-splash | hard rubber in wood crate | thimble | Traction |

| | | | | | | | | | | |
|----------|----|-------------|------|----------------------------------------|----|----|------------|-----------------------------|----------------|-----------------------------------------------------------|
| FC 40234 | 30 | 290 (5 hr.) | 920 | 35 | 27 | 16 | non-splash | hard rubber in | thimble | Traction |
| FC 40230 | 30 | 420 (5 hr.) | 1350 | in 5 wood trays totalling o/a 41 34 16 | | | non-splash | hard rubber in | thimble | Traction |
| FC 40231 | 40 | 129 (5 hr.) | 590 | 29 | 21 | 15 | non-splash | 5 wood trays | | |
| FC 40400 | 48 | 115 (5 hr.) | 710 | 34 | 24 | 11 | non-splash | hard rubber in wood crate | thimble | Traction |
| FC 40233 | 48 | 290 (5 hr.) | 1245 | in 3 wood trays 2 each 40 15 17 | | | non-splash | hard rubber in wood crates | thimble | Traction |
| ZB 14124 | 80 | 5 (100 hr.) | 52 | 40 | 8 | 17 | non-splash | hard rubber in 3 wood trays | | |
| | | | | 1 each 40 8 17 | | | | glass in wood crate | studs and nuts | B off 6140 99-910-1529 in wood crate with carrying handle |

SECTION Z9

CHARGER, BATTERY, METAL RECTIFIER

These are listed in voltage order.

Charging rate and quantities of cells are for acid/lead acid except where stated

| Cat. No. | INPUT | | | OUTPUT | | | MOUNTING | DIMENSIONS | | | WEIGHT lb. | Climatic condition | I.S.P.L. Code No. |
|------------------|--------------------|-------|--------|----------|--------|-------|-----------------------|------------|----------|----------|---------------|-----------------------|----------------------|
| | Volts Min. Max. | Phase | Cycles | Circuits | Amps. | Cells | | L in. | W in. | H in. | | | |
| Z9/ | | | | | | | | | | | | | |
| 6130-99-942-6286 | 90 250 | 1 | 40-60 | 1 | 10 | 6 | Wall | 17 | 12 | 16 | 64 | Temperate | ES 157 |
| 6130-99-942-6361 | 90 250 | 1 | 50 | 1 | 15-30 | 6 | Bench or Wall | 12 | 18 | 24 | 70 | Temperate | ES 158B |
| 6130-99-942-6292 | 100 125 200 250 | 1 | 50 | 1 | 10 | 2-96 | Wall | 30 | 21 | 23 | 300 | Temperate | ES 132B |
| 6130-99-943-7403 | 100 125 | 1 | 50-60 | 2 | 10 | 3-24 | Floor | 26 | 23 | 30 | 300 | Tropical | |
| 6130-99-110-2246 | 100 230 | 1 | 50-60 | 1 | 10-20 | 6-12 | Floor Wall or Rack | 20 | 13 | 11 | 35 | Tropical | |
| 6130-99-942-6295 | 100 120 | 1 | 40-60 | 1 | 1.5-16 | 6 | Bench or Wall | 16 | 12 | 16 | 65 | Tropical | ES 1117 |
| 6130-99-942-6293 | 100 250 | 1 | 50-100 | 1 | 15 | 3-54 | Floor | 36 | 25 | 48 | 868 | Tropical | ES 1456 |
| 6130-99-942-6288 | 110 230 | 1 | 50-60 | 1 | 12-6 | 6-12 | Bench or Wall | 20 | 12 | 11 | 28 | Tropical | ES 1117 |
| 6130-99-942-7909 | 110 250 | 1 | 50-60 | 1 | 7 | 3 | Portable | 5 | 3 | 3 | 4 | Temperate | |

| | | | | | | | | | | | | | |
|------------------|---------|---|-------|---|------|-------|-------------------------------|----|----|----|-----|-----------|---------|
| 6130-99-942-6284 | 180 230 | 1 | 50 | 1 | 12 | 8 | Floor | 19 | 12 | 26 | 66 | Temperate | |
| ZJ 00282 | 190 250 | 1 | 50 | 1 | 30 | 20 | Wall | 23 | 21 | 33 | 230 | Tropical | ES 1382 |
| 6130-99-110-2260 | 190 250 | 1 | 50 | 1 | 16 | 15 | Wall | 31 | 18 | 23 | 210 | Temperate | |
| 6130-99-942-6366 | 200 250 | 1 | 40-60 | 1 | 40 | 30 | Wall | 36 | 21 | 33 | 377 | Temperate | |
| 6130-99-942-6290 | 200 250 | 1 | 50 | 1 | 8 | 1-100 | Wall, Floor or Bench | 30 | 21 | 23 | 300 | Tropical | ES 2612 |
| 6130-99-942-6291 | 200 250 | 1 | 50 | 1 | 10 | 3-60 | Floor | 26 | 23 | 30 | 300 | Tropical | |
| ZJ 00313 | 200 250 | 1 | 50 | 1 | 11.6 | 12 | Bench, Wall or Rack | 19 | 11 | 27 | 150 | Tropical | |
| 6130-99-110-0535 | 200 250 | 1 | 50 | 1 | 20 | 14 | Wall | 28 | 19 | 30 | - | - | |
| 6130-99-942-9874 | 200 250 | 1 | 50 | 1 | 26 | 8 | Wall | 15 | 11 | 25 | 73 | Tropical | |
| 6130-99-942-9875 | 200 250 | 1 | 50 | 1 | 30 | 12 | Wall | 15 | 11 | 25 | 96 | Temperate | |
| 6130-99-900-5082 | 200 250 | 1 | 50 | 1 | 30 | - | Portable w. engine starter | 13 | 14 | 10 | 37 | - | |

SECTION Z9

CHARGER, BATTERY, METAL RECTIFIER - continued

| Cat. No. | INPUT | | | OUTPUT | | | MOUNTING | DIMENSIONS | | | WEIGHT lb. | Climatic condition | I.S.P.L. Code No. |
|------------------|--------------------|-------|--------|----------|------------|----------------|-------------------------------|------------|----------|----------|---------------|-----------------------|----------------------|
| | Volts Min. Max. | Phase | Cycles | Circuits | Amps. | Cells | | L in. | W in. | H in. | | | |
| Z9/ | | | | | | | | | | | | | |
| 6130-99-901-7973 | 200 250 | 1 | 50 | 1 | 100 | - | Trolley Mounted | 15 | 19 | 29 | - | Temperate | |
| 6130-99-900-4267 | 200 250 | 1 | 50 | 1 | 50 100 | - | Trolley Mounted | 25 | 19 | 35 | 200 | - | |
| ZJ 00180 | 200 250 | 1 | 50 | 2 | 6-12 | 36 | Floor w. engine starter | 30 | 34 | 47 | 336 | Temperate | |
| 6130-99-942-6285 | 200 250 | 1 | 50 | 3 | 1 | 1-36 | Bench or Wall | 25 | 21 | 20 | 200 | Tropical | ES 2687 |
| 6130-99-942-6289 | 200 250 | 1 | 50 | 3 | 2 4 | 1-36 3-18 | Wall | | | | | | |
| 6130-99-942-6289 | 200 250 | 1 | 50 | 3 | 5.5 5.5 | 12-24 12-24 | Floor | 34 | 25 | 37 | 382 | Tropical | |
| 6130-99-900-5083 | 200 250 | 1 | 50-60 | 1 | 10 22 | 12-24 | Portable w. engine starter | 29 | 21 | 31 | - | - | |

| | | | | | | | | | | | | | |
|------------------|--------------------|---|----------|---|--------|------------------|---------------|----|----|----|-----|-----------|---------|
| 6130-99-110-0536 | 230 | 1 | 50 | 1 | 48 | 24 (Alkaline) | - | - | - | - | - | - | |
| 6130-99-942-6287 | 240 | 1 | 50 | 1 | .25 | 12 | Wall | 8 | 3 | 5 | 8 | Tropical | |
| ZJ 00305 | 240 | 1 | 50 | 1 | 4 | 12 | Wall | 16 | 10 | 23 | 70 | Tropical | |
| 6130-99-942-6365 | 250 | 1 | 50 | 1 | 11 | 24 | Wall | 15 | 11 | 25 | 73 | Temperate | 11734 |
| 6130-99-942-6367 | 250 | 1 | 50 | 1 | 20 | 15 | Wall | 23 | 21 | 33 | 200 | Temperate | |
| 6130-99-942-9879 | 250 | 1 | 50 | 1 | 30 | 16 | Wall | 31 | 18 | 23 | 224 | Temperate | |
| ZJ 00306 | 250 | 1 | 50 | 1 | 30 | 18 | - | - | - | - | - | - | 12949 |
| 6130-99-942-6362 | 250 | 1 | 50 | 1 | 30 | 20 | Wall | 23 | 18 | 33 | 235 | Temperate | ES 2845 |
| 6130-99-942-9877 | 250 | 1 | 50 | 1 | 30 | 32 | Wall | 33 | 21 | 33 | 336 | Tropical | |
| 6130-99-942-9878 | 250 | 1 | 50 | 1 | 40 | 18 | Wall or Floor | 33 | 17 | 36 | 250 | Tropical | |
| 6130-99-942-6296 | 200 220 400 440 | 3 | 60 50 | 2 | 10-120 | 6-12 | Floor | 26 | 18 | 57 | 504 | Tropical | ES 2328 |
| 6130-99-942-9880 | 200 220 400 440 | 3 | 60 50 | 2 | 10-120 | 6-12 | Floor | 26 | 18 | 57 | 504 | Tropical | ES 2328 |
| 6130-99-110-2000 | 415 | 3 | 50 | 2 | 10-120 | 6-12 | Floor | 32 | 19 | 43 | 500 | - | |

SECTION Z9

| Cat. No. | Item name or designation | Item description or detail | I.S.P.L. Code No. |
|---------------------|-------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|
| 29/8125-99-942-4991 | JAR, ELECTROLYTE, 1 GAL. | Glass; round; approx. 6.3/16 dia. x 14.1/4 in. high. Neck size 1.3/8 I.D. x 1.7/8 in. O.D. w. grooved rubber Stopper closing inside and outside of neck | |
| 29/6130-99-900-5213 | PLUG-SOCKET, ELECTRICAL RELAY, BATTERY CHARGE TIMING 6/36 cells, mercury switch | Comprising:- A voltage measuring thermal device and synchronous motor-driven timing element. The thermal device consists of a Sunvic type 611C thermal relay (29/ZJ 00210) Charging supply is automatically disconnected at end of measured time. Fitted with mercury switch (29/ZJ 00308) | |
| 29/5945-99-943-4793 | M.J. V5 | Voltage adjustment is carried out by 2 variable resistances Supplied in rear connected metal case w. moulded insulation front plate together w. 3 fixing brackets for flush mounting | |
| 29/ZJ 00307 | M.J. V6 | Din. 6.15 high x 5.13 wide x 9.8 in. o/a deep Voltage adjustment is carried out by variable resistances Surface mounted | |
| 29/ZJ 00284 | SULPHURIC ACID, Electrolyte | 1270 specific gravity at 60° F. B.S. 3031 10 gal. unit quantity in glass carboy in hamper | |

SECTION Z9

INDEX TO CATALOGUE NUMBERS

| Cat. No. | Page | Cat. No. | Page | Cat. No. | Page |
|-------------|------|---------------------|------|---------------------|------|
| Z9/5J 3305 | 7 | Z9/ZJ 00300 | 8 | Z9/6130-99-942-7909 | 10 |
| Z9/5J 3306 | 5 | Z9/ZJ 00305 | 13 | | |
| | | Z9/ZJ 00306 | 13 | | |
| Z9/AN 605 | 5 | Z9/ZJ 00307 | 14 | Z9/6130-99-942-9874 | 11 |
| | | Z9/ZJ 00313 | 11 | Z9/6130-99-942-9875 | 11 |
| | | | | Z9/6130-99-942-9877 | 13 |
| Z9/FC 40230 | 9 | | | Z9/6130-99-942-9878 | 13 |
| Z9/FC 40231 | 9 | Z9/5945-99-943-4793 | 14 | Z9/6130-99-942-9879 | 13 |
| Z9/FC 40233 | 9 | | | Z9/6130-99-942-9880 | 13 |
| Z9/FC 40234 | 9 | | | | |
| | | Z9/6130-99-110-0535 | 11 | Z9/6130-99-942-9880 | 13 |
| Z9/FC 40400 | 9 | Z9/6130-99-110-0536 | 13 | | |
| | | | | Z9/6140-99-104-0636 | 6 |
| Z9/WB 2673 | 5 | | | | |
| | | Z9/6130-99-110-2000 | 13 | Z9/6140-99-110-2470 | 5 |
| | | | | Z9/6140-99-110-2684 | 6 |
| Z9/ZB 0276 | 5 | | | | |
| Z9/ZB 0536 | 7 | | | Z9/6140-99-900-2321 | 6 |
| Z9/ZB 0955 | 5 | Z9/6130-99-110-2246 | 10 | Z9/6140-99-900-2672 | 5 |
| Z9/ZB 0970 | 5 | Z9/6130-99-110-2260 | 11 | Z9/6140-99-900-3149 | 4 |
| | | | | Z9/6140-99-900-3265 | 7 |
| Z9/ZB 10064 | 5 | | | Z9/6140-99-900-5663 | 3 |
| Z9/ZB 11277 | 5 | Z9/6130-99-900-4267 | 12 | Z9/6140-99-900-6133 | 6 |
| Z9/ZB 13680 | 7 | | | Z9/6140-99-900-7951 | 6 |
| Z9/ZB 13729 | 7 | | | Z9/6140-99-900-8938 | 7 |
| Z9/ZB 13731 | 7 | | | | |
| Z9/ZB 13832 | 7 | Z9/6130-99-900-5082 | 11 | | |
| | | Z9/6130-99-900-5083 | 12 | Z9/6140-99-910-1501 | 5 |
| | | | | Z9/6140-99-910-1502 | 5 |
| Z9/ZB 14124 | 9 | | | Z9/6140-99-910-1504 | 5 |
| Z9/ZB 14595 | 5 | Z9/6130-99-900-5213 | 14 | Z9/6140-99-910-1506 | 5 |
| | | | | Z9/6140-99-910-1509 | 6 |
| Z9/ZJ 00008 | 5 | | | Z9/6140-99-910-1510 | 6 |
| | | | | Z9/6140-99-910-1511 | 5 |
| Z9/ZJ 00118 | 7 | Z9/6130-99-901-7973 | 12 | Z9/6140-99-910-1513 | 6 |
| Z9/ZJ 00127 | 4 | | | Z9/6140-99-910-1514 | 6 |
| Z9/ZJ 00128 | 7 | | | Z9/6140-99-910-1515 | 7 |
| | | | | Z9/6140-99-910-1524 | 7 |
| Z9/ZJ 00174 | 6 | Z9/6130-99-942-6284 | 11 | Z9/6140-99-910-1529 | 7 |
| Z9/ZJ 00175 | 8 | Z9/6130-99-942-6285 | 12 | Z9/6140-99-910-1545 | 7 |
| Z9/ZJ 00176 | 6 | Z9/6130-99-942-6286 | 10 | | |
| Z9/ZJ 00180 | 6 | Z9/6130-99-942-6287 | 13 | | |
| Z9/ZJ 00188 | 12 | Z9/6130-99-942-6288 | 10 | Z9/6140-99-910-1802 | 4 |
| Z9/ZJ 00193 | 7 | Z9/6130-99-942-6289 | 12 | Z9/6140-99-910-1803 | 4 |
| | | Z9/6130-99-942-6290 | 11 | Z9/6140-99-910-1809 | 4 |
| Z9/ZJ 00212 | 8 | Z9/6130-99-942-6291 | 11 | Z9/6140-99-910-1810 | 4 |
| Z9/ZJ 00232 | 8 | Z9/6130-99-942-6292 | 10 | Z9/6140-99-910-1815 | 4 |
| Z9/ZJ 00234 | 6 | Z9/6130-99-942-6293 | 10 | Z9/6140-99-910-1816 | 4 |
| Z9/ZJ 00253 | 6 | Z9/6130-99-942-6295 | 10 | Z9/6140-99-910-1817 | 4 |
| Z9/ZJ 00270 | 6 | Z9/6130-99-942-6296 | 13 | | |
| Z9/ZJ 00276 | 7 | | | Z9/6140-99-94-9413 | |
| Z9/ZJ 00280 | 8 | | | | |
| Z9/ZJ 00281 | 6 | Z9/6130-99-942-6361 | 10 | | |
| Z9/ZJ 00282 | 11 | Z9/6130-99-942-6362 | 13 | Z9/6140-99-94-9955 | |
| Z9/ZJ 00283 | 5 | Z9/6130-99-942-6365 | 13 | | |
| Z9/ZJ 00284 | 14 | Z9/6130-99-942-6366 | 11 | | |
| Z9/ZJ 00285 | 8 | Z9/6130-99-942-6367 | 13 | Z9/6125-99-942-4997 | 14 |

RESTRICTED.